



## Section 1 - Identification of The Material and Supplier

Lucas Oil Products of Australia Pty Ltd  
Unit 2/5-7 Meakin Rd  
Meadowbrook, Qld 4131

Phone: 07 3299 6320 (office hours)  
Phone 0407 751 175 (24/7)  
Fax: 07 3299 7365

**Chemical nature:** Solvent blend.  
**Trade Name:** Lucas Anti-Gel Cold Weather Diesel Fuel Treatment  
**Product Code:** 10865, 10866, 10867, 10868, 20865, 20866  
**Product Use:** Prevent cold filter plugging in diesel and bio-diesel fuels.  
**Creation Date:** August, 2016  
**This version issued:** August, 2016 and is valid for 5 years from this date.  
**Poisons Information Centre:** Phone 13 1126 from anywhere in Australia

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Xn, Harmful. N, Dangerous to the environment. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

**SUSMP Classification:** S5

**ADG Classification:** None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

**UN Number:** None allocated



### GHS Signal word: DANGER

Flammable liquids Category 4

Aspiration Hazard Category 1

Carcinogenicity Category 2

Hazardous to aquatic environment Short term/Chronic Category 3

### HAZARD STATEMENT:

H227: Combustible liquid.

H304: May be fatal if swallowed and enters airways.

H351: Suspected of causing cancer.

H412: Harmful to aquatic life with long lasting effects.

### PREVENTION

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P262: Do not get in eyes, on skin, or on clothing.

P273: Avoid release to the environment.

P281: Use personal protective equipment as required.

### RESPONSE

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P308+P313: If exposed or concerned: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

### STORAGE

P402+P404: Store in a dry place. Store in a closed container.

## SAFETY DATA SHEET



P403+P235: Store in a well-ventilated place. Keep cool.

**DISPOSAL**

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

**Emergency Overview**

**Physical Description & Colour:** Clear, dark amber coloured liquid.

**Odour:** Characteristic odour.

**Major Health Hazards:** limited evidence of a carcinogenic effect, if aspirated, may cause lung damage.

**Section 3 - Composition/Information on Ingredients**

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Kerosene	8008-20-6	>60	not set	not set
Aromatic hydrocarbons	64742-94-5	10-30	not set	not set
Naphthalene	91-20-3	1-5	52	79

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

**Section 4 - First Aid Measures****General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

**Section 5 - Fire Fighting Measures**

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam, water fog.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

**Flash point:** 63°C, Closed cup

**Upper Flammability Limit:** No data.

**Lower Flammability Limit:** No data.

**Autoignition temperature:** No data.

**Flammability Class:** Flammable Category 4 (GHS), C1 combustible (AS 1940)

**Section 6 - Accidental Release Measures**

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Eye/face

**SAFETY DATA SHEET**



protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Note that this product is GHS Flammable Class 4 and therefore, for Storage, meets the definition of Dangerous Goods. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: **AS/NZS 4501** set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Naphthalene	52	79

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: rubber, PVC.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Clear, dark amber coloured liquid.
<b>Odour:</b>	Characteristic odour.
<b>Boiling Point:</b>	182-288°C at 100kPa
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	No specific data. Expected to be low at 100°C.
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	No data.

## SAFETY DATA SHEET



Specific Gravity:	0.824
Water Solubility:	Negligible.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Viscosity:	Kinematic (40°C): 0.03 cm <sup>2</sup> /s (3 cSt)
Autoignition temp:	No data.

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Keep containers tightly closed. Containers should be kept dry.

**Incompatibilities:** bases, oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

### Local Effects:

**Target Organs:** There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Kerosene	Conc>=10%: Xn; R65
• Aspiration hazard - category 1	
Aromatic Hydrocarbons	Conc>=10%: Xn; R65
• Aspiration hazard - category 1	
Naphthalene	>=1%Conc<25%: Xn; R40
• Carcinogenicity - category 2	
• Acute toxicity - category 4	
• Hazardous to the aquatic environment (acute) - category 1	
• Hazardous to the aquatic environment (chronic) - category 1	
<b>Kerosene:</b> LD <sub>50</sub> Oral, Rat 15000mg/kg	
<b>Naphthalene:</b> LD <sub>50</sub> Oral, Rat 490mg/kg	LD <sub>50</sub> Dermal, Rabbit = >20,000mg/kg

## Potential Health Effects

### Inhalation:

**Short Term Exposure:** Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term inhalation.

### Skin Contact:

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short Term Exposure:** This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

## SAFETY DATA SHEET

**Ingestion:**

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

**Carcinogen Status:**

**SWA:** Naphthalene is classified by SWA as a Class 3 Carcinogen, possibly carcinogenic to humans.

See the SWA website for further details. A web address has not been provided as addresses frequently change.

**NTP:** Naphthalene is classified by NTP as reasonably anticipated to be carcinogenic to humans.

See the NTP website for further details. A web address has not been provided as addresses frequently change.

**IARC:** Naphthalene is classed 2b IARC - possibly carcinogenic to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

---

**Section 12 - Ecological Information**

---

Harmful to aquatic organisms, may cause long-term adverse effects to the aquatic environment. Insufficient data to be sure of status.

For Naphthalene:

Acute EC<sub>50</sub> 1600 µg/L Fresh water Daphnia - *Daphnia magna* - Neonate 48 hours

Acute LC<sub>50</sub> 2350 µg/L Marine water Crustaceans - *Palaemonetes pugio* 48 hours

Acute LC<sub>50</sub> 213 µg/L Fresh water Fish - *Melanotaenia fluviatilis* - Larvae 96 hours

Chronic NOEC 0.67 ppm Fresh water Fish - *Oncorhynchus kisutch* 40 days

---

**Section 13 - Disposal Considerations**

---

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

---

**Section 14 - Transport Information**

---

**UN Number:** This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

---

**Section 15 - Regulatory Information**

---

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredients: Kerosene, Aromatic hydrocarbons, Naphthalene, are mentioned in the SUSMP.

---

**Section 16 - Other Information**

---

This SDS contains only safety-related information. For other data see product literature.

**Acronyms:**

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

**SAFETY DATA SHEET**





**Product Name: Lucas Anti-Gel Cold Weather Diesel Fuel Treatment**

**Page: 6 of 6**

**This version issued: August, 2016**

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

**Please read all labels carefully before using product.**

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, August, 2016.

<http://www.kilford.com.au/> Phone (02)9251 4532

## **SAFETY DATA SHEET**

Issued by: Lucas Oil Products of Australia Pty Ltd

Phone: 07 3299 6320 (office hours)

**Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)**